ClickShare CX-20

Transform small meeting rooms and huddle spaces into inspiring conference facilities.



- Full BYOD support
- Remote collaboration
- Triple agnostic: works with any device, and UC technology and any brand of AV peripheral
- Enhanced security
- Connected and cloud managed
- Delivered with 1 Conferencing Button
- Collaborate with Conferencing Button or Collaboration App

The modern world of enterprise requires smooth collaboration and flexibility, especially when it comes to team meetings in huddle rooms, and this is exactly what Barco ClickShare CX-20 provides. Encouraging creative innovation through seamless wireless conferencing, ClickShare CX-20 can make meetings more inspiring and more productive.

Find out what's new in the latest ClickShare update

Start a huddle meeting from your device

With ClickShare CX-20, it's easier than ever to start remote huddle meetings from your device, bringing a seamless and immersive conferencing experience to all participants, whether local, guest or remote. Use your preferred conferencing software combined with the ClickShare Conferencing Button and you can start your conference in less than seven seconds. The CX-20 connects wirelessly to existing huddle room cameras, speakerphones and audio peripherals, saving time and maximizing efficiency.

Decide how you want to collaborate

ClickShare CX-20 provides you with exceptional flexibility and choice, enabling you to decide just how you want to collaborate. Whether you're on PC, Mac or mobile, the ClickShare Wireless Conferencing Button and ClickShare Collaboration App facilitate a user experience that's both straightforward and consistent. In addition to its multi-device compatibility, ClickShare CX-20 is also fully compatible with your conferencing platform (UC) technology and your brand of USB-peripherals. Additional features such as local view of the room display help to optimize the experience.



ClickShare CX-20 Barco



Enhanced security and seamless integration

A perfect fit for any business environment, the ClickShare CX-20 wireless conferencing system comes equipped with a selection of great features for enhanced security and seamless integration. ClickShare Conference provides hassle-free integration with any IT network, while the XMS (Cloud) Management Platform provides for easy device management, as well as an intuitive user experience and clear analytics to get more out of your digital workspace. For practical questions on network deployment of the ClickShare Conference range, check our technical support or get in touch with your Barco contact

PRODUCT SPECIFICATIONS

CLICKSHARE CX-20

nmm x 135 mm x 135 mm Indiard 110/220 V AC plug Indiard 110/220 V AC plug
erational: 5-10W, 24W Max gr dows 8/8.1/10. macOS 10.13 and higher. roid y9 and higher (ClickShare App)* 12 and higher (ClickShare App)* JHD (3840*2160) @ 30Hz. HDMI 1.4b s, HDMI JSB-A, 1 X USB-C
dows 8/8.1/10. macOS 10.13 and higher. roid v9 and higher (ClickShare App)* 12 and higher (ClickShare App)* UHD (3840*2160) @ 30Hz. HDMI 1.4b 6, HDMI USB-A, 1 X USB-C
dows 8/8.1/10. macOS 10.13 and higher. roid v9 and higher (ClickShare App)* 12 and higher (ClickShare App)* JHD (3840*2160) @ 30Hz. HDMI 1.4b J., HDMI JSB-A, 1 X USB-C
dows 8/8.1/10. macOS 10.13 and higher. roid v9 and higher (ClickShare App)* 12 and higher (ClickShare App)* UHD (3840*2160) @ 30Hz. HDMI 1.4b HDMI USB-A, 1 X USB-C
roid v9 and higher (ClickShare App)* 12 and higher (ClickShare App)* UHD (3840*2160) @ 30Hz. HDMI 1.4b HDMI USB-A, 1 X USB-C ktop & Mobile*
roid v9 and higher (ClickShare App)* 12 and higher (ClickShare App)* UHD (3840*2160) @ 30Hz. HDMI 1.4b HDMI USB-A, 1 X USB-C ktop & Mobile*
JSB-A, 1 X USB-C ktop & Mobile*
USB-A, 1 X USB-C ktop & Mobile*
ktop & Mobile*
<u> </u>
<u> </u>
lay, Google Cast, Miracast*
. 25dBA @ 0-30°C . 30dBA @ 30-40°C
A2-PSK in stand alone mode A2-PSK or IEEE 802.1X using the ClickShare Button in network integration mode
802.11 a/g/n/ac and IEEE 802.15.1
30m (100 ft) between ClickShare Button and ClickShare Base Unit quency band 2.4 GHZ and 5 GHz (DFS)
GHZ and 5 GHz (DFS channels supported in select number of countries)
thernet LAN 1Gbit ISB Type-C 2.0 (front); 1x USB Type A 2.0 (front)
erating: 0°C to +40°C (+32°F to +104°F) :: 35°C (95°F) at 3000m :age: -20°C to +60°C (-4°F to +140°F)
age: 0 to 90% relative humidity, non-condensing eration: 0 to 85% relative humidity, non-condensing
sington lock
C/CE
al view of the room display only
& WiFi *
ar standard. 5 years coverage via SmartCare
· · · · · · · · · · · · · · · · · · ·
1 C t J : : : : : : : : : : : : : : : : : :

Last updated: 25 Aug 2020

 $Technical\ specifications\ are\ subject\ to\ change\ without\ prior\ notice.\ Please\ check\ www.barco.com\ for\ the\ latest\ information.$

