

UC-B30-Z

Crestron Flex Wall Mount Small Room Video Conference System for Zoom Rooms™ Software



- *Front-of-room video conferencing solution for Zoom Rooms™ software*
- *Native Zoom Rooms touch screen UI provides a consistent user experience with simple operation and one-touch meeting joins*
- *Complete kit contains a 10.1 in. touch screen, Crestron® smart soundbar and camera, UC bracket assembly, and PoE injector— just add a display and mount*
- *Easy to specify and install — no custom design, programming, or software installation required*
- *Network management and provisioning and system alerts through the XiO Cloud® service*
- *Enterprise-grade security - connects and communicates securely over any enterprise or SMB network*
- *Supports a single video display*

The Crestron Flex UC-B30-Z system provides a video conference room solution for use with Zoom Rooms software. It supports a single video display¹ and features a 10.1 in. touch screen (TS-1070-B-S), UC Bracket Assembly (UC-BRKT-200-S-Z-ASSY), and Crestron UC video conference smart soundbar & camera (UC-SB1-CAM-FLEX).

Native Zoom Rooms™ Software Experience

The UC-B30-Z system features Zoom Rooms conferencing software that enables audio and video connectivity for easy collaboration and content sharing.

Intuitive User Interface

With a large 10.1 in. (257 mm) capacitive touch screen display, the Crestron® tabletop touch screen (TS-1070-B-S) provides superior conferencing control in meeting rooms, huddle spaces, and executive offices. The touch screen also offers optional control of room lighting, shades, thermostats, and other equipment.²

Simplified Deployment

The UC Bracket Assembly (UC-BRKT-200-S-Z-ASSY) provides preassembled components on one ready-to-mount bracket to simplify installation. The assembly can be mounted on a wall, or it can be attached to the rear of the display device.

High-Definition Video Conferencing with Impressive Audio

High-quality speakers, microphone, and digital signal processing deliver exceptional full-duplex speakerphone performance from the Crestron UC video conference soundbar and camera (UC-SB1-CAM-FLEX). The built-in conferencing camera captures the room in HD 1080p video resolution and with an ultra-wide 150° diagonal field of view.

Enterprise-Grade Security

Crestron Flex is an enterprise-grade solution that is ideally equipped for mass deployment throughout any sized corporate, university, medical, military, or government facility.

Easy Provisioning and Device Management

The XiO Cloud service³ is an IoT cloud based provisioning service that enables installers and IT managers to deploy and manage thousands of devices easily. The XiO Cloud service allows for system alerts, network management and provisioning, and the pairing of a control device to the system's UC Engine. System updates are controlled by Windows® software update.

Visit www.crestron.com/xiocloud for additional information.

Deployment Resources

View the [Crestron Flex Pre-Deployment Checklist](#) to help plan your Crestron Flex installation.

UC-B30-Z

Crestron Flex Wall Mount Small Room Video Conference System for Zoom Rooms™ Software

Specifications

Included Components

TS-1070-B-S	10.1 in. (257 mm) tabletop touch screen, black
UC-BRKT-200-S-Z-ASSY	UC Bracket Assembly for Zoom Rooms systems, comprised of: <ul style="list-style-type: none">• UC-ENGINE-S-Z: UC Engine for Zoom Rooms video• HD-CONV-USB-200: HDMI® to USB 3.0 converter for content ingest• Mounting hardware
UC-SB1-CAM-FLEX	UC Video Conference Smart Soundbar and Camera
CBL-CAT5E-7	Ethernet LAN cable for UC Engine, RJ45-to-RJ45, black, 7 ft (2.1 m)
CBL-HD-6	HDMI Interface Cable, 6 ft (1.8 m)
CBL-HD-20	HDMI Interface Cable, 20 ft (6.1 m)
PWE-4803RU	PoE Injector
EDID Passthrough	HDMI Female-to-Male

Tabletop Touch Screen

Touch Screen	10.1 in. (257 mm) diagonal capacitive multi-touch TFT active matrix color LCD, 1920 x 1200 pixels
UI	Zoom Rooms UI plus optional Crestron Smart Graphics® room control UI ²
Ethernet	100 Mbps, auto switching, auto negotiating, auto discovery, full/half duplex, TCP/IP, UDP/IP, CIP, DHCP, SSL, TLS, SSH, SFTP (SSH File Transfer Protocol), IEEE 802.1X, SNMP, IPv4 or IPv6, Active Directory® service authentication, HTTPS web browser setup, XiO Cloud® client, IEEE 802.3at compliant

Power over Ethernet

IEEE 802.3at Type 2 compliant PoE+ PD (Powered Device); Normally requests 15 W from an 802.3at Type 2 PSE with LLDP advanced power management; With room scheduling and USB enabled, requests 18 W from an 802.3at Type 2 PSE with LLDP; Requests 30 W (PoE+ Class 4) from an 802.3at Type 2 PSE without LLDP; Requests 15.4 W (PoE Class 0) from an 802.3af (or 802.3at Type 1) PSE

PoE Injector

A PoE injector is included to power the touch screen if network PoE is not available

Construction

Plastic, smooth black finish, edge-to-edge glass with black surround

Dimensions

Height: 5.29 in. (134 mm)
Width: 9.63 in. (245 mm)
Depth: 4.67 in. (119 mm)

Weight

2.44 lb (1105 g)

Smart Soundbar and Camera

Speakers

Stereo 2-way, 20 W per channel; 3 in. (76 mm) woofers; 3 x 4-3/8 in. (76 x 112 mm) passive radiators; 1 in. (25 mm) dome tweeters; 80 Hz to 20 kHz (±3 dB) frequency response; 91 dB SPL @ 1 m output level (both channels driven at full power)

Microphone

Linear quad-element far-field adaptive beamforming microphone array; 15 ft (4.6 m) pickup range,⁴ 180° horizontal pickup angle; 20 Hz to 8 kHz frequency response

Audio DSP

Acoustic echo cancellation, dereverberation, automatic gain control, dynamic noise suppression, adaptive beamforming, speaker volume control, speaker EQ and limiting (fixed); Full-duplex IEEE 1329 Type 1 compliant

Camera Optics

12 Megapixel 1/2.3 CMOS sensor, ultra wide angle six element aspherical glass lens, f/2.8 aperture

UC-B30-Z

Crestron Flex Wall Mount Small Room Video Conference System for Zoom Rooms™ Software

Camera Field of View	150° diagonal, 120° horizontal, 90° vertical	Content Ingest	HDMI input via HDMI to USB 3.0 converter (model HD-CONV-USB-200)
Autozoom	Genius Framing automatic lossless digital zoom intelligently frames around people in the room	Display Output	Single display support
Camera Noise Reduction	3D noise reduction, bias compensating spatio-temporal filtering, wide area chroma filtering, flicker elimination	Display Output Resolution	1080p
Camera Scaling	Real-time scaling, dewarping, and perspective correction	Power	65 W via external 100-240 VAC, 50/60 Hz adapter (included)
Camera Resolution	HD 1080p @ 30 fps	Construction	Metal mounting bracket, black, preassembled with UC-ENGINE-S-Z and HD-CONV-USB-200
Analog Audio Input	2-Channel stereo via 3.5 mm TRS mini-phone jack, fixed level (bypasses DSP), 1 Vrms maximum per channel for full rated output, for in-room amplification of an external audio source	Mounting	Surface wall mount behind the display device, or attach to the rear of the display device via the bolts attaching the display to a VESA® compliant display mount; Bracket includes mounting holes on both side edges, spaced 100, 200, and 300 mm vertically, to allow for attachment to either side of the display mounting plate
Analog Audio Output	2-Channel stereo via 3.5 mm TRS mini-phone jack, fixed level, 1 Vrms maximum, feeds amplified audio content to an assistive listening system	Dimensions	Height: 15.00 in. (381 mm) Width: 14.50 in. (368 mm) Depth: 1.72 in. (44 mm)
Status Bar	Multi-segment RGBY LED zero-center mutually-diverging linear bargraph	Weight	6.64 lb (3 kg)
Main Power	24 VDC via external 100-240 VAC, 50/60 Hz power pack, model PW-2420RU (included)	Models	
Enclosure	Lightly textured gunmetal black finish, plastic housing, perforated stainless steel grilles, die-cast aluminum rear cover, integral steel hinged mounting bracket	UC-B30-Z	Crestron Flex Wall Mount Small Room Video Conference System for Zoom Rooms™ Systems
Mounting	Freestanding or surface wall mount at ear/face level (adhesive feet included, mounting bracket attached)	Available Accessories	
Dimensions	Height: 4.57 in. (116 mm), 4.64 in. (118 mm) with feet Width: 43.60 in. (1107 mm) Depth: 3.90 in. (99 mm)	SW-XIOC-EM	XiO Cloud® Provisioning and Management Service, Endpoint Management License
Weight	13.56 lb (6.2 kg)	SW-XIOC-S	XiO Cloud® Provisioning and Management Service, Support License
		SW-XIOC-API	XiO Cloud® Provisioning and Management Service, REST API License

UC Bracket Assembly

Mini PC	Intel Core® processor with Windows® 10 IOT Edition OS
UC Client	Zoom Rooms software
Management Client	XiO Cloud Service

UC-B30-Z

Crestron Flex Wall Mount Small Room Video Conference System for Zoom Rooms™ Software

Notes:

1. Display must support "Wake on Sync" and "Sleep on No Sync" functionality. Consult the display manufacturer's specifications or internal settings of the specific display.
2. Room control capability (lighting, shades, thermostats, etc.) requires additional equipment and commissioning to be provided by a Crestron authorized integrator and/or programmer. Additional costs may apply.
3. The XiO Cloud service is a room based subscription service available separately.
4. Microphone pickup range may vary in rooms with highly reflective infrastructure (e.g., glass walls, metal furniture, open ceilings, etc.) or above average ambient noise.

This product may be purchased from select authorized Crestron dealers and distributors. To find a dealer or distributor, please contact the Crestron sales representative for your area. A list of sales representatives is available online at www.crestron.com/How-To-Buy/Find-a-Representative or by calling 855-263-8754.

This product is covered under the Crestron standard limited warranty. Refer to www.crestron.com/warranty for full details.

The specific patents that cover Crestron products are listed online at patents.crestron.com.

Certain Crestron products contain open source software. For specific information, please visit www.crestron.com/opensource.

Crestron, the Crestron logo, Smart Graphics, and XiO Cloud are either trademarks or registered trademarks of Crestron Electronics, Inc. in the United States and/or other countries. Active Directory and Windows are either trademarks or registered trademarks of Microsoft Corporation in the United States and/or other countries. HDMI is either a trademark or registered trademark of HDMI Licensing LLC in the United States and/or other countries. Intel Core is either a trademark or registered trademark of Intel Corporation in the United States and/or other countries. VESA is either a trademark or registered trademark of Video Electronics Standards Association in the United States and/or other countries. Zoom Rooms is either a trademark or registered trademark of Zoom Video Communications, Inc. in the United States and/or other countries. Other trademarks, registered trademarks, and trade names may be used in this document to refer to either the entities claiming the marks and names or their products. Crestron disclaims any proprietary interest in the marks and names of others. Crestron is not responsible for errors in typography or photography.

Specifications are subject to change without notice.



©2020 Crestron Electronics, Inc.

Rev 10/07/20

UC-B30-Z

Crestron Flex Wall Mount Small Room Video Conference System for Zoom Rooms™ Software


Touch Screen (TS-1070-B-S)



UC-B30-Z

Crestron Flex Wall Mount Small Room Video Conference System for Zoom Rooms™ Software

UC Bracket Assembly (UC-BRKT-200-S-Z-ASSY)



UC-B30-Z

Crestron Flex Wall Mount Small Room Video Conference System for Zoom Rooms™ Software

Smart Soundbar and Conferencing Camera (UC-SB1-CAM-FLEX)

