

# UC-BX30-Z

## Crestron Flex Advanced Wall Mount Small Room Video Conference System for Zoom Rooms™ Software



- *Front-of-room video conferencing solution for Zoom Rooms™ software*
- *Present, call, conference, and collaborate using your own device's UC conference platform (BYOD) or the native Zoom Rooms platform*
- *Native Zoom Rooms touch screen UI provides a consistent user experience with simple operation and one-touch meeting joins*
- *Complete kit contains a 10.1 in. touch screen, Crestron® smart soundbar and camera, UC Bracket Assembly, and UC Presentation Transmitter— just add a display(s) and mount*
- *Easy to specify and install — no custom design, programming, or software installation required*
- *Network management and provisioning and system alerts through the XiO Cloud® service*
- *Premium-level service with Crestron Flex Care (optional)*
- *Enterprise-grade security - connects and communicates securely over any enterprise or SMB network*

The Crestron Flex UC-BX30-Z system provides a video conference room solution for use with Zoom Rooms software. It supports single or dual video displays<sup>1</sup> and features a 10.1 in. touch screen ([TS-1070-B-S](#)), UC Bracket Assembly (UC-BRKT-250-P-Z-ASSY), UC Presentation Transmitter (UC-PR), and Crestron UC video conference smart soundbar & camera (UC-SB1-CAM-FLEX).

### Native Zoom Rooms™ Software Experience

The UC-BX30-Z system features Zoom Rooms conferencing software that enables audio and video connectivity for easy collaboration and content sharing.

### Intuitive User Interface

With a large 10.1 in. (257 mm) capacitive touch screen display, the Crestron® tabletop touch screen ([TS-1070-B-S](#)) provides

superior conferencing control in meeting rooms, huddle spaces, and executive offices. The touch screen also offers optional control of room lighting, shades, thermostats, and other equipment.<sup>2</sup>

### Simplified Deployment

The UC Bracket Assembly (UC-BRKT-250-P-Z-ASSY) provides preassembled components on one ready-to-mount bracket to simplify installation. The assembly can be mounted on a wall, or it can be attached to the rear of the display device.

### High-Definition Video Conferencing with Impressive Audio

High-quality speakers, microphone, and digital signal processing deliver exceptional full-duplex speakerphone performance from the Crestron UC video conference soundbar and camera (UC-SB1-CAM-FLEX). The built-in conferencing camera captures the room in HD 1080p video resolution and with an ultra-wide 150° diagonal field of view.

### Bring Your Own Device (BYOD)

Conference room visitors can connect their laptop to the Crestron Flex system to use their own UC conference platform. The UC Presentation Transmitter (UC-PR) switches to the connected laptop's UC platform and returns to the native Zoom Rooms platform when disconnected.

### Enterprise-Grade Security

Crestron Flex is an enterprise-grade solution that is ideally equipped for mass deployment throughout any sized corporate, university, medical, military, or government facility.

### Easy Provisioning and Device Management

The XiO Cloud service<sup>3</sup> is an IoT cloud based provisioning service that enables installers and IT managers to easily deploy and manage thousands of devices. The XiO Cloud service allows for system alerts, network management and provisioning, and the pairing of a control device to the system's UC Engine. System updates are controlled by Windows® software update.

Visit [www.crestron.com/xiocloud](http://www.crestron.com/xiocloud) for additional information.

### Premium-Level Support

Crestron Flex Care is an optional subscription service that automatically renews annually, providing 24/7 live remote technical support, an extended five year warranty on Crestron® hardware, expedited advance replacements, and a discounted rate for on-site support.

Visit [www.crestron.com/flexcare](http://www.crestron.com/flexcare) for additional information.

### Deployment Resources

View the [Crestron Flex Pre-Deployment Checklist](#) to help plan your Crestron Flex installation.

# UC-BX30-Z

Crestron Flex Advanced Wall Mount Small Room Video Conference System for Zoom Rooms™ Software

## Specifications

### Included Components

<b>TS-1070-B-S</b>	10.1 in. (257 mm) tabletop touch screen, black
<b>UC-BRKT-250-P-Z-ASSY</b>	UC Bracket Assembly for Zoom Rooms systems, comprised of: <ul style="list-style-type: none"><li>• UC-ENGINE-P-Z: UC Engine for Zoom Rooms video</li><li>• ADPT-USB-ENET: USB-to-Ethernet Adapter</li><li>• HD-CONV-USB-: CAT5 to USB 3.0 converter for content ingest</li><li>• Mounting hardware</li></ul>
<b>UC-PR</b>	UC Presentation Transmitter
<b>UC-SB1-CAM-FLEX</b>	UC Video Conference Smart Soundbar and Camera
<b><u>CBL-4K-DP-HD-6</u></b>	Active Converter Cable, DisplayPort™ to HDMI, 18 Gbps, 6 ft (1.8 m)
<b><u>CBL-CAT5E-7</u></b>	(3) Ethernet LAN cable for UC Engine, RJ45-to-RJ45, black, 7 ft (2.1 m)
<b><u>CBL-HD-6</u></b>	HDMI Interface Cable, 6 ft (1.8 m)
<b><u>DM-CBL-ULTRA-PC-20</u></b>	Ethernet LAN cable, CAT6a, RJ45-to-RJ45, blue, 20 ft (6.1 m)

### Tabletop Touch Screen

<b>Touch Screen</b>	10.1 in. (257 mm) diagonal capacitive multi-touch TFT active matrix color LCD, 1920 x 1200 pixels
<b>UI</b>	Zoom Rooms UI plus optional Crestron Smart Graphics® room control UI <sup>2</sup>
<b>Ethernet</b>	100 Mbps, auto switching, auto negotiating, auto discovery, full/half duplex, TCP/IP, UDP/IP, CIP, DHCP, SSL, TLS, SSH, SFTP (SSH File Transfer Protocol), IEEE 802.1X, SNMP, IPv4 or IPv6, Active Directory® service authentication, HTTPS web browser setup, XiO Cloud® client, IEEE 802.3at compliant

### Power over Ethernet

IEEE 802.3at Type 2 compliant PoE+ PD (Powered Device); Normally requests 15 W from an 802.3at Type 2 PSE with LLDP advanced power management; With room scheduling and USB enabled, requests 18 W from an 802.3at Type 2 PSE with LLDP; Requests 30 W (PoE+ Class 4) from an 802.3at Type 2 PSE without LLDP; Requests 15.4 W (PoE Class 0) from an 802.3af (or 802.3at Type 1) PSE

### Power

Powered via PoE passthrough on the UC-PR

### Construction

Plastic, smooth black finish, edge-to-edge glass with black surround

### Dimensions

Height: 5.29 in. (134 mm)  
Width: 9.63 in. (245 mm)  
Depth: 4.67 in. (119 mm)

### Weight

2.44 lb (1105 g)

### Smart Soundbar and Camera

#### Speakers

Stereo 2-way, 20 W per channel; 3 in. (76 mm) woofers; 3 x 4-3/8 in. (76 x 112 mm) passive radiators; 1 in. (25 mm) dome tweeters; 80 Hz to 20 kHz (±3 dB) frequency response; 91 dB SPL @ 1 m output level (both channels driven at full power)

#### Microphone

Linear quad-element far-field adaptive beamforming microphone array; 15 ft (4.6 m) pickup range,<sup>4</sup> 180° horizontal and 180° vertical pickup angle; 20 Hz to 8 kHz frequency response

#### Audio DSP

Acoustic echo cancellation, dereverberation, automatic gain control, dynamic noise suppression, adaptive beamforming, speaker volume control, speaker EQ and limiting (fixed); Full-duplex IEEE 1329 Type 1 compliant

#### Camera Optics

12 Megapixel 1/2.3 CMOS sensor, ultra wide angle six element aspherical glass lens, f/2.8 aperture

#### Camera Field of View

150° diagonal, 120° horizontal, 90° vertical

# UC-BX30-Z

## Crestron Flex Advanced Wall Mount Small Room Video Conference System for Zoom Rooms™ Software

<b>Autozoom</b>	Genius Framing automatic lossless digital zoom intelligently frames around people in the room	<b>Display Output Resolution</b>	1080p
<b>Camera Noise Reduction</b>	3D noise reduction, bias compensating spatio-temporal filtering, wide area chroma filtering, flicker elimination	<b>Power</b>	90 W via external 100-240VAC, 50/60 Hz adapter (included)
<b>Camera Scaling</b>	Real-time scaling, dewarping, and perspective correction	<b>Construction</b>	Metal mounting bracket, black, preassembled with UC-ENGINE-P-Z and HD-CONV-USB-250
<b>Camera Resolution</b>	HD 1080p @ 30 fps	<b>Mounting</b>	Surface wall mount behind the display device, or attach to the rear of the display device via the bolts attaching the display to a VESA® compliant display mount; Bracket includes mounting holes on both side edges, spaced 100, 200, and 300 mm vertically, to allow for attachment to either side of the display mounting plate
<b>Analog Audio Input</b>	2-Channel stereo via 3.5 mm TRS mini-phone jack, fixed level (bypasses DSP), 1 Vrms maximum per channel for full rated output, for in-room amplification of an external audio source	<b>Dimensions</b>	Height: 15.00 in. (381 mm) Width: 14.50 in. (368 mm) Depth: 1.72 in. (44 mm)
<b>Analog Audio Output</b>	2-Channel stereo via 3.5 mm TRS mini-phone jack, fixed level, 1 Vrms maximum, feeds amplified audio content to an assistive listening system		
<b>Status Bar</b>	Multi-segment RGBY LED zero-center mutually-diverging linear bargraph		
<b>Main Power</b>	24 VDC via external 100-240 VAC, 50/60 Hz power pack, model <a href="#">PW-2420RU</a> (included)		
<b>Enclosure</b>	Lightly textured gunmetal black finish, plastic housing, perforated stainless steel grilles, die-cast aluminum rear cover, integral steel hinged mounting bracket		
<b>Mounting</b>	Freestanding or surface wall mount at ear/face level (adhesive feet included, mounting bracket attached)		
<b>Dimensions</b>	Height: 4.57 in. (116 mm), 4.64 in. (118 mm) with feet Width: 43.60 in. (1107 mm) Depth: 3.90 in. (99 mm)		
<b>Weight</b>	13.56 lb (6.2 kg)		

### UC Bracket Assembly

<b>Mini PC</b>	Intel Core® processor with Windows® 10 IOT Edition OS
<b>UC Client</b>	Zoom Rooms software
<b>Management Client</b>	XiO Cloud Service
<b>Content Ingest</b>	HDMI input via CAT5 to USB 3.0 converter (model HD-CONV-USB-250)
<b>Display Output</b>	Single or dual display support

### UC Presentation Transmitter

<b>Video Input Signal Types</b>	HDMI, DisplayPort 1.2 via USB Type-C® port
<b>Video Output Signal Types</b>	HDMI over CAT5
<b>Resolution</b>	1080p
<b>Video Content Protection</b>	HDCP 1.4 and HDCP 2.2
<b>Audio Input Signal Types</b>	HDMI, DisplayPort 1.2 via USB Type-C port
<b>Audio Output Signal Types</b>	HDMI over CAT5
<b>Communications</b>	Ethernet: 100 Mbps, auto-switching, auto negotiating, auto-discovery HDMI over CAT5: HDCP, Ethernet HDMI: HDCP USB: USB 2.0 and USB 3.0

# UC-BX30-Z

## Crestron Flex Advanced Wall Mount Small Room Video Conference System for Zoom Rooms™ Software

### Connectors

LAN PoE: (1) 8-pin RJ-45 connector, female;  
ACC: (1) USB 3.0 Type B connector, female;  
For firmware loading only;  
USB A: (1) USB 2.0 Type A connector, female;  
USB B: (1) USB 2.0 Type B connector, female;  
USB-C: (1) USB 2.0 Type-C connector, female;  
HDMI IN: (1) HDMI Type A, female;  
To RX: (1) 8-pin RJ-45 connector, female;  
Power Jack: (1) DC power connector;  
LAN: (1) 8-pin RJ-45 connector, female;  
Ground: (1) 6-32 screw

### Indicators

PWR: (1) Green LED, indicates operating power supplied via power supply  
Ethernet: (2) LEDs on To RX port; Green indicates Ethernet link status;  
Amber indicates Ethernet activity

### Power Supply

24VDC, 3.75A, 100-240VAC, 90 W

### Device Charging

Up to 60 W charging for devices connected via USB-C® port

### Construction

Metal, black finish, integral mounting flanges;  
Vented top, front, bottom, and sides

### Mounting

Surface mount for mounting under table;  
Attaches to a single rack rail

### Dimensions

Height: 1.58 in. (40 mm)  
Width: 9.25 in. (235 mm)  
Depth: 8.20 in. (208 mm)

## Models

### UC-BX30-Z

Crestron Flex Advanced Wall Mount Small Room Video Conference System for Zoom Rooms™ Software

## Available Accessories

For a list of available accessories, visit the [UC-BX30-Z](#) product page.

### Notes:

1. Display must support "Wake on Sync" and "Sleep on No Sync" functionality. Consult the display manufacturer's specifications or internal settings of the specific display.
2. Room control capability (lighting, shades, thermostats, etc.) requires additional equipment and commissioning to be provided by a Crestron authorized integrator and/or programmer. Additional costs may apply.
3. The XiO Cloud service is a room based subscription service available separately.
4. Microphone pickup range may vary in rooms with highly reflective infrastructure (e.g., glass walls, metal furniture, open ceilings, etc.) or above average ambient noise.

This product may be purchased from select authorized Crestron dealers and distributors. To find a dealer or distributor, please contact the Crestron sales representative for your area. A list of sales representatives is available online at [www.crestron.com/How-To-Buy/Find-a-Representative](http://www.crestron.com/How-To-Buy/Find-a-Representative) or by calling 855-263-8754.

This product is covered under the Crestron standard limited warranty. Refer to [www.crestron.com/warranty](http://www.crestron.com/warranty) for full details.

The specific patents that cover Crestron products are listed online at [patents.crestron.com](http://patents.crestron.com).

Certain Crestron products contain open source software. For specific information, please visit [www.crestron.com/opensource](http://www.crestron.com/opensource).

Crestron, the Crestron logo, Smart Graphics, and XiO Cloud are either trademarks or registered trademarks of Crestron Electronics, Inc. in the United States and/or other countries. HDMI is either a trademark or registered trademark of HDMI Licensing LLC in the United States and/or other countries. Intel Core is either a trademark or registered trademark of Intel Corporation in the United States and/or other countries. Active Directory and Windows are either trademarks or registered trademarks of Microsoft Corporation in the United States and/or other countries. USB Type-C and USB-C are either trademarks or registered trademarks of USB Implementers Forum, Inc. in the United States and/or other countries. DisplayPort and VESA are either trademarks or registered trademarks of Video Electronics Standards Association in the United States and/or other countries. Zoom Rooms is either a trademark or registered trademark of Zoom Video Communications, Inc. in the United States and/or other countries. Other trademarks, registered trademarks, and trade names may be used in this document to refer to either the entities claiming the marks and names or their products. Crestron disclaims any proprietary interest in the marks and names of others. Crestron is not responsible for errors in typography or photography.

Specifications are subject to change without notice.



©2020 Crestron Electronics, Inc.

Rev 12/05/20

# UC-BX30-Z

Crestron Flex Advanced Wall Mount Small Room Video Conference System for Zoom Rooms™ Software


## TS-1070-B-S



# UC-BX30-Z

Crestron Flex Advanced Wall Mount Small Room Video Conference System for Zoom Rooms™ Software


## UC-BRKT-250-P-Z-ASSY



# UC-BX30-Z

Crestron Flex Advanced Wall Mount Small Room Video Conference System for Zoom Rooms™ Software

## UC-PR



# UC-BX30-Z

Crestron Flex Advanced Wall Mount Small Room Video Conference System for Zoom Rooms™ Software

## UC-SB1-CAM-FLEX

