

UC-FCM-Z

Crestron Flex R-Series Plus Mobile UC System for Zoom Rooms™ Software



- *Rapid deployment mobile UC system for presenting, calling, conferencing, and collaborating*
- *Supports Zoom Rooms™ conferencing software*
- *Utilizes the Crestron Mercury® console to provide a superior conferencing and collaboration experience*
- *Includes an intelligent Huddly IQ™ camera with a 150° field of view (CCS-CAM-USB-F-400)*
- *20 ft microphone range with 360° quad array*
- *Supports most 50 in. to 60 in. displays (not included)*
- *Easy to provision and manage with the XiO Cloud® service*
- *Enterprise-grade security for connecting and communicating over any enterprise or SMB network*

The Crestron Flex R-Series Plus mobile UC system can be rapidly deployed to provide convenient video conferencing in a variety of professional settings, such as corporate, education, healthcare, or manufacturing environments. A Crestron unified communications engine assembly comes pre-installed for easy component installation and hookup. All components mount to a wheeled cart to bring collaboration to wherever it is needed.

Native Zoom Rooms™ Software Experience

R-Series UC systems feature Zoom Rooms conferencing software for easy collaboration and content sharing.

Crestron Mercury® Tabletop Console

The included Crestron Mercury Tabletop Console (CCS-UC-1) provides superior conferencing and collaboration for R-Series systems. The CCS-UC-1 delivers a simple and consistent user experience through its large 7 in. HD color touch screen. Its integrated AEC-enabled USB speakerphone affords full-duplex wideband audio performance.

Huddly IQ™ Camera

The included Huddly IQ camera features an ultra wide-angle 150° diagonal field of view to capture any space in Full HD 1080p video resolution. High precision aspherical optics, 12 MP CMOS sensor, and advanced video processing ensure a clear video image free from light or noise artifacts. Genius Framing digital autozoom intelligently detects the people in the room and frames them for an optimal view.

UC Engine Assembly

Zoom Rooms video conferencing solutions are powered by the UC Engine (UC-ENGINE-SD-Z), a powerful Intel® NUC Mini PC running Zoom Rooms software. The UC Engine Assembly (UC-BRKT-100-SD-Z-ASSY) streamlines the installation of a Crestron® UC system by providing the UC Engine on one ready-to-mount bracket that attaches to the inside frame of an R-Series mobile UC system.

For more information, refer to the [UC-BRKT-100-SD-Z-ASSY](#) product page.

XiO Cloud® Provisioning and Management Service

Crestron Flex R-Series systems are enterprise grade solutions that are equipped for mass deployment. R-Series systems are easily manageable with the XiO Cloud service, an IoT (Internet of Things) based platform for remotely provisioning, monitoring, and managing Crestron devices. The service allows for the deployment and management of thousands of devices in the amount of time it previously took to manage just one. Advanced security features ensure privacy, reliability, and compliance with your organization's IT policies.

For more information, visit www.crestron.com/xiocloud.

Deployment Resources

View the [Crestron Flex Pre-Deployment Checklist](#) to help plan your Crestron Flex installation.

UC-FCM-Z

Crestron Flex R-Series Plus Mobile UC System for Zoom Rooms™ Software

Specifications

Included Components

Wheeled Cart	Metal frame comprised of: (4) Caster wheels; Display mounting bracket; Custom shelving for Crestron components; Power and Ethernet cable retractors
CCS-UC-1	Crestron Mercury Tabletop UC Audio Conference Console; Cable, CAT5e, RJ-45 Male - RJ-45 Male, 12 ft (3.66 m); Cable, USB 2.0, A - Micro B, 6 ft (1.83 m); Retention Plate, Cable Tie Wrap
CCS-CAM-USB-F-400	Huddly IQ camera
UC-BRKT-100-SD-Z-ASSY	UC Engine Assembly, comprised of: UC-ENGINE-SD-Z: UC Engine for Zoom Rooms video; HD-CONV-USB-200: HDMI to USB 3.0 converter for content ingest; UC-CONN-HD: EDID emulator for UC Engine display output; Mounting bracket
CBL-CAT5E-7	Ethernet LAN cable for UC Engine, RJ45-to-RJ45, black, 7 ft (2.1 m)
CBL-HD-20	HDMI cable for content source, Type A male-to-male, 20 ft (6.1 m)
CBL-USB-A-BMICRO-6	USB Cable, USB Type A Male to Micro-B Male, 6 ft (1.83 m)
CBL-USB-A-EXT-15	USB Extension Cable, USB Type A Male-to-Female, 15 ft (4.57 m)
CBL-USBC-HD-9	USB-C® to HDMI converter cable, USB Type-C® male to HDMI Type A male, 9 ft (2.74 m)
CEN-SW-POE-5	5-Port POE switch
PW-2420RU	Desktop power pack, 24 VDC, 2.5 A, 2.1 mm

Crestron Mercury Conferencing Console

Touch Screen	7 in. (178 mm) diagonal capacitive multi-touch TFT active matrix color LCD, 1280 x 800 pixels
---------------------	---

UI

Mic Mute Symbol and Light Bar

Zoom Rooms UI

(2) Capacitive buttons with bi-color LEDs;
Either button toggles between mute and unmute;
The symbol LED flashes green when the unit is powering up;
All LEDs illuminate red when the mic is muted;
All LEDs illuminate green when the mic is unmuted during an active call or online meeting

AEC

Limes Audio TrueVoice® acoustic echo cancellation, automatic mic mixing, automatic gain control, and dynamic noise reduction;
Full-duplex IEEE 1329 Type 1 compliant

Speaker

Full range speaker, 11 W amplifier power, 95 dB SPL at 0.5 m with maximum output, 90 Hz to 22 kHz frequency response

Microphones

360° quad mic array, 20 ft (6.1 m) typical pickup range

Extension Microphones

Supports two mic pods, model CCS-UCA-MIC KIT (sold separately)

Occupancy Sensor

Patent-pending Persistent Occupancy Awareness combining passive infrared motion and voice activity detection, 6 ft (1.83 m) PIR range in front of touch screen, sensor activates touch screen and reports room occupancy to Crestron Fusion® monitoring and scheduling software

Ethernet

10/100 Mbps;
Enterprise grade security and management including IEEE 802.1X, Active Directory® authentication, LDAP, Kerberos, SSL, TLS, SSH, SFTP (SSH File Transfer Protocol), SRTP, digest access authentication, password login, HTTPS secure provisioning, Crestron XiO Cloud client, IEEE 802.3at Type 2 compliant

USB

USB 2.0 micro Type B device port, supports UAC for audio interface to UC Engine (cable included)

UC-FCM-Z

Crestron Flex R-Series Plus Mobile UC System for Zoom Rooms™ Software

Power	24 VDC via external 100-240 VAC, 50/60 Hz power pack, model PW-2420RU (included)
Dimensions	Height: 4.11 in. (105 mm) Width: 8.92 in. (227 mm) Depth: 12.74 in. (324 mm)
Weight	5.5 lb (2.5 kg)

Refer to the [CCS-UC-1](#) product page for additional information.

Camera

Model	Huddly IQ
Field of View	150° diagonal, 120° horizontal, 90° vertical
Connectivity	Plug-and-play USB 3.1
Resolution/FPS	HD 1080p @ 30 fps
Dimensions	Height: 1.30 in. (33 mm) Width: 1.58 in. (40 mm) Depth: 2.82 in. (72 mm)
Weight	4.1 oz (115 g)

Refer to the [CCS-CAM-USB-F-400](#) product page for additional information.

UC Engine Assembly

Mini PC	Intel® NUC Kit NUC8i5BEK
Processor	Intel Core® i5-8259U processor (2.3 GHz with 3.8GHz Turbo, Quad Core, Hyper-thread, 6 MB Cache, 28W TDP)
UC Client	Zoom Rooms Software
Management Client	XiO Cloud Service
USB	USB 3.0 host supporting USB HID, UAC, and UVC for audio conference soundbar, camera, content ingest, and keyboard/mouse devices
Content Ingest	HDMI input via HDMI to USB 3.0 converter (model HD-CONV-USB-200)
Display Output	Single display support (USB-C® primary, HDMI output)
Camera Input Resolution	HD 1080p @ 30 fps
Display Output Resolution	HD 1080p @ 60 fps
Power	90 W via external 100-240 VAC, 50/60 Hz adapter (included)

Construction	Metal mounting bracket, black, preassembled with UC Engine and USB to HDMI converter
Mounting	Surface wall mount behind the display device, or attach to the rear of the display device via the bolts attaching the display to a VESA® compliant display mount; the bracket includes mounting holes on both side edges, spaced 100, 200, and 300 mm vertically, to allow for attachment to either side of the display mounting plate
Dimensions	Height: 16.00 in. (407 mm) Width: 14.00 in. (356 mm) Depth: 1.68 in. (43 mm)

Refer to the [UC-ENGINE-SD-Z](#), [HD-CONV-USB-200](#), and [UC-BRKT-100-SD-Z-ASSY](#) product pages for additional information.

Wheeled Cart

Wheels	(4) Casters
Cable Management	Ethernet cable retractor; Power cable retractor; Cable management kit consisting of (2) large and (2) small openings
Display Mounting	VESA® compliant mounting bracket for 50 in. to 60 in. displays
Device Mounting	Custom shelf beneath the display mounting bracket for the included Crestron Mercury device
Construction	Steel subframe
Dimensions	Height: 68.9 in. (1750 mm) without display and display bracket Width: 43.5 in. (1105 mm) without display and display bracket Usable Depth: 4.3 in. (109 mm)
Cart Weight	206 lbs
Capacity Weight	190 lbs
Compliance	UL® listed for US and Canada

UC-FCM-Z

Crestron Flex R-Series Plus Mobile UC System for Zoom Rooms™ Software

Models

UC-FCB-T

Crestron Flex R-Series Mobile UC System for Microsoft Teams® Rooms

UC-FCB-Z

Crestron Flex R-Series Mobile UC System for Zoom Rooms™ Software

UC-FCM-T

Crestron Flex R-Series Plus Mobile UC System for Microsoft Teams® Rooms

UC-FCM-Z

Crestron Flex R-Series Plus Mobile UC System for Zoom Rooms™ Software

UC-FCMX-T

Crestron Flex R-Series Plus Mobile UC System with BYOD Support for Microsoft Teams® Rooms

UC-FCMX-Z

Crestron Flex R-Series Plus Mobile UC System with BYOD Support for Zoom Rooms™ Software

UC-FCM-U

Crestron Flex R-Series Plus Mobile UC System with Universal Platform Support

Included Accessories

CCS-UC-1

Crestron Mercury® UC Conference Console

CCS-CAM-USB-F-400

Huddly IQ™ Collaboration Camera

UC-BRKT-100-SD-Z-ASSY

UC Engine Assembly with UC-ENGINE-SD-Z and HD-CONV-USB-200

CBL-CAT5E-7

CAT5e Cable, RJ45-to-RJ45, Black, 7 ft (2.1 m)

CBL-HD-20

Crestron® Certified HDMI® Interface Cable, 18 Gbps, 20 ft (6.1 m)

CBL-USB-A-BMICRO-6

USB Cable, USB Type A Male to Micro-B Male, 6 ft (1.83 m)

CBL-USB-A-EXT-15

USB Extension Cable, USB Type A Male-to-Female, 15 ft (4.57 m)

CBL-USBC-HD-9

USB-C® to HDMI® Converter Cable, USB Type-C® Male to HDMI Type A Male, 9 ft (2.74 m)

CEN-SW-POE-5

5-Port PoE Switch

PW-2420RU

Desktop Power Pack, 24 VDC, 2.5 A, 2.1 mm

This product may be purchased from select authorized Crestron dealers and distributors. To find a dealer or distributor, please contact the Crestron sales representative for your area. A list of sales representatives is available online at www.crestron.com/How-To-Buy/Find-a-Representative or by calling 855-263-8754.

This product is covered under the Crestron standard limited warranty. Refer to www.crestron.com/warranty for full details.

The specific patents that cover Crestron products are listed online at patents.crestron.com.

Certain Crestron products contain open source software. For specific information, please visit www.crestron.com/opensource.

Crestron, the Crestron logo, Crestron Fusion, Crestron Mercury, and XiO Cloud are either trademarks or registered trademarks of Crestron Electronics, Inc. in the United States and/or other countries. Active Directory and Microsoft Teams are either trademarks or registered trademarks of Microsoft Corporation in the United States and/or other countries. HDMI is either a trademark or registered trademark of HDMI Licensing LLC in the United States and/or other countries. Huddly IQ is either a trademark or registered trademark of Huddly AS in the United States and/or other countries. Intel and Intel Core are either trademarks or registered trademarks of Intel Corporation in the United States and/or other countries. TrueVoice is either a trademark or registered trademark of Google Inc. in the United States and/or other countries. USB-C and USB Type-C are either trademarks or registered trademarks of USB Implementers Forum, Inc. in the United States and/or other countries. UL is either a trademark or registered trademark of Underwriters Laboratories, Inc. in the United States and/or other countries. VESA is either a trademark or registered trademark of Video Electronics Standards Association in the United States and/or other countries. Zoom Rooms is either a trademark or registered trademark of Zoom Video Communications, Inc. in the United States and/or other countries. Other trademarks, registered trademarks, and trade names may be used in this document to refer to either the entities claiming the marks and names or their products. Crestron disclaims any proprietary interest in the marks and names of others. Crestron is not responsible for errors in typography or photography.

Specifications are subject to change without notice.

©2020 Crestron Electronics, Inc.

Rev 06/18/20

UC-FCM-Z

Crestron Flex R-Series Plus Mobile UC System for Zoom Rooms™ Software

UC-FCM-T, UC-FCM-Z, UC-FCMX-T, UC-FCMX-Z

