

RoboFLIP 30 HDBT

In-Ceiling Rotating PTZ Camera

ORDERING INFORMATION

999-99800-000 (North America)

999-99800-001 (Europe/UK)

999-99800-009 (Australia/New Zealand)

OVERVIEW

The RoboFLIP 30 HDBT camera fully rotates into its enclosure when in standby mode, allowing room occupants full assurance that video feeds are not active. With its unique “flipping” design and Vaddio’s industry-leading Tri-Synchronous Motion technology, the camera silently rotates, providing ultra-smooth, simultaneous pan, tilt and zoom functions for natural camera motion.

The RoboFLIP 30 HDBT is the ultimate professional PTZ camera solution for both security and design-conscious customers, yet maintains Vaddio’s high standards for performance, network manageability and ease of use.

Equipped with 30x optical zoom, the RoboFLIP 30 HDBT camera captures stunning high definition video from greater distances. Place the RoboFLIP 30 HDBT in a corporate board room, law office, courtroom, medical institution, or any application where it’s critical to clearly know the camera’s active status or maintain clean lines.

The recessed design of the RoboFLIP 30 HDBT allows staff to easily clean and sanitize rooms when necessary without the risk of damaging fragile camera components.

The camera’s HDBaseT output allows for flexible installation options - power with a PoE+ network switch or mid-span power injector for an IP streaming configuration, or connect to an HDBaseT video switch or OneLINK extension system for a variety of video outputs. Compare OneLINK systems to choose from output options such as HD-SDI, HDMI, USB 3.0 and IP streaming.

Control the camera through Telnet, RS-232, the included IR remote, or the Vaddio Device Controller touch panel. With its modern web-based user interface, integrators can adjust 16 stored PTZ presets, color, white balance and focus, access system diagnostic logs, streaming settings and more. With built-in network connection via the HDBT port, the camera system is compatible with remote management tools like the free Vaddio Deployment Tool application.

Building on Vaddio’s successful architectural camera line, the RoboFLIP 30E HDBT camera is simple and straightforward to install. The camera has only one connection point, an HDBT port, that provides PoE+ power, video, control, and network connection to the camera. Clean lines and minimalistic design provide another great architectural videoconferencing solution for interior designers.



FEATURES

- 8.51 Megapixel (8.57 Total MP), full HD (native 1080p/60) image sensor
- 30x zoom, horizontal field of view of 70.2°
- Smooth, silent BLDC direct-drive motors for precise pan and tilt movements at up to 120° per second
- Simultaneous HDBaseT and IP (H.264) streaming at resolutions up to 1080p/30
- Pairs with Vaddio OneLINK receivers
- Presenter-friendly IR remote control
- Control through Telnet, serial RS-232 or the Vaddio Device Controller
- Full administrative control via web interface; manage remotely while monitoring the stream separately.



The RoboFLIP 30 HDBT features one HDBaseT output

TECHNICAL SPECIFICATIONS

Outputs/protocols	HDBaseT, IP (H.264)
Aspect ratio	IP (H.264) Streaming: 16:9, 3:2 and 4:3
IP Streaming resolutions/frame rates	Simultaneous IP (RTSP or RTMP format with H.264 compression) up to 1080p/30
Image device	1/2.5-Type Exmor R CMOS sensor
Pixels	8.51 million; (8.57M Total Megapixels)
Lens and Horizontal FOV	30x zoom, 20 x optical zoom + 10x IntelliZoom, f=4.4mm wide end to 88.4mm tele end, F2 to F3.8
Pan angle and speed	±160°, 0.35°/sec to 120°/sec
Tilt angle and speed	+90, -30°, 0.35°/sec to 120°/sec
Min. working distance	80mm (wide), 800mm (tele)
Min. illumination	1.6 lux; 100+ lux recommended
Backlight compensation	On/off
Aperture/detail	16 steps
Focusing system	Auto Focus / Manual Focus Mode / One-push Trigger Mode
Gain	Auto / Manual (0 to 33 dB)
White balance	Auto, ATW, Indoor, Outdoor, One-push, Manual
S/N ratio	More than 50 dB
Power	PoE+
Remote management	IR Remote, web interface, Telnet, RS-232 command APIs and Vaddio Device Controller
Enhanced Wide Dynamic Range	Yes
Spotlight Compensation Mode	Yes
Noise Reduction	Yes
Presets	16 + Custom Home
Invertible	Yes
Motors	Silent BLDC Direct Drive Motors
Warranty	2 years plus option for purchasing additional 3 years
Weight	15 lbs (6.80 kg)
Height	9.25" (235 mm)
Diameter	16" (406 mm)
Operating/storage temperature	0°C to +40°C (32°F to 104°F)
Operating/storage humidity (relative)	20% to 80% RH, non-condensing

Specifications are subject to change without notice.

WHAT'S IN THE BOX

- RoboFLIP 30 HDBT camera
- White trim ring including IR receiver and courtesy light button with 3 qty mounting screws
- Tile Support Brace
- Vaddio IR remote commander for RoboFLIP 30 HDBT camera
- Installation Guide



THE ART OF EASY | legrandav.com

USA P 800.572.2011 E av.vaddio.support@legrand.com
EMEA P +31.495.580.840 E av.emea.sales@legrand.com
APAC P +852.2145.4099 E av.asia.sales@legrand.com



©2020 Legrand AV Inc. 200404 07/2020 Vaddio is a registered trademark of Legrand AV Inc. All other brand names or marks are used for identification purposes and are trademarks of their respective owners. All patents are protected under existing designations. Other patents pending.

COMMERCIAL AV BRANDS
 C2G | Chief | Da-Lite | Luxul | Middle Atlantic | Projecta | Vaddio | Wiremold