

# AM-TX3-200

## AirMedia® Series 3 Connect Endpoint



- Streamlines connectivity to personal devices via a single USB-C® connection or through HDMI and USB connections
- Supports content sharing up to 4K30 resolution and provides access to in-room conferencing peripherals
- Flexible installation and deployment options, including mounting under tables, in podiums, and other locations using the supplied bracket
- Versatile power options, including PoE, DC power, or USB-C via a connected user device
- With DC power, PoE+ passthrough is available to power a connected touch screen
- Compatible with Wi-Fi®-enabled AirMedia® Series 3 Receivers
- Communicates with an AirMedia Receiver using Wi-Fi Direct, Infrastructure Wi-Fi, or a wired network
- No software or driver installation required

The AirMedia® Series 3 Connect Endpoint ([AM-TX3-200](#)) enables wireless presentation and conferencing<sup>1</sup> when paired with a Wi-Fi® network capable AirMedia Series 3 Receiver. Deploy the AM-TX3-200 alongside a compatible AirMedia receiver in conference rooms, huddle spaces, classrooms, or almost any space to establish a productive meeting or learning environment.

### A Complete System Solution

The AM-TX3-200 works alongside a compatible AirMedia receiver to provide a complete system solution. The AM-TX3-200 communicates with the AirMedia receiver using a point-to-point Wi-Fi Direct connection, an infrastructure Wi-Fi network, or a wired network.

### Simple Connectivity

A personal device can be connected to the AM-TX3-200 using either a single USB-C® cable<sup>2</sup> or a combination of a USB-A cable<sup>2</sup> and an HDMI® cable<sup>2</sup>, supporting a wide variety of devices (cables sold separately). No drivers, software, or applications are required, offering a simple and user-friendly experience.

### Rapid, High-Resolution Presentation

The AM-TX3-200 leverages USB-C and HDMI for native video communication, eliminating the need for software installation on personal devices. Simply connect and start presenting to the in-room display with up to 4K30 resolution within seconds.

### Seamless Conferencing

When the AM-TX3-200 is connected to a personal device via USB, the user can access in-room conferencing peripherals<sup>3</sup> connected to a paired Wireless Conferencing-capable AirMedia Receiver ([AM-3100-WF](#), [AM-3200-WF](#), [AM-3100-WF-I](#), or [AM-3200-WF-I](#)). These peripherals can then be used on the personal device with unified communications software such as Microsoft Teams® or Zoom® software.

### Flexible Deployment Options

The AM-TX3-200 is designed to be deployed in a variety of spaces with unique power, connectivity, and installation requirements. The device can be powered via PoE, DC power, or the connected user device via USB-C. When powered with a local power supply ([PW-2420RU](#)), PoE+ is available to a device connected to the AUX port, such as a touch screen.

The device is shipped with a bracket, ensuring secure mounting and easy installation.

**NOTE:** When using USB-C to power the device, only the USB-C input is active. The AM-TX3-200 wired network interfaces will not function in this mode.

### Enterprise-Grade Security

The AirMedia platform is an enterprise-grade solution that can be deployed across hundreds of spaces, and set up easily using just a web browser, Crestron Fusion® software, or the XiO Cloud® service. It employs standard network security protocols, including 802.1x network access control, Active Directory® authentication, and AES content encryption to protect privacy and ensure compliance with your organization's IT policies.

# AM-TX3-200

## AirMedia® Series 3 Connect Endpoint

### Specifications

#### Communications

<b>Ethernet</b>	100/1000 Mbps, autoswitching, autonegotiating, full/half duplex, TCP/IP, UDP/IP, DHCP, SSL, TLS, 802.3af compliant
<b>Wi-Fi</b>	Dual-band Wi-Fi 6 802.11a/b/g/n/ac/ax (2.4 GHz & 5 GHz); Up to 70 ft (23 m) range at 80 Mbps, subject to site-specific conditions; Refer to <a href="#">Wireless Best Practices</a> for more information.
<b>HDMI Input</b>	HDCP 1.4, EDID
<b>USB</b>	USB 2.0
<b>OS Support</b>	Windows 10, Windows 11, macOS® 11 or newer

#### Video

<b>Input Signal Types</b>	DisplayPort™ Alt Mode over USB-C; HDMI
<b>Output Signal Types</b>	Network stream, received by a paired AirMedia Series 3 receiver
<b>Maximum Resolution</b>	3840x2160@30Hz (2160p30); Output resolution is determined by the HDMI® output on a paired AirMedia Series 3 receiver

**NOTE:** All video inputs will be scaled to the selected HDMI output resolution.

#### Audio

<b>Input Signal Types</b>	DisplayPort Alt Mode over USB-C; HDMI
<b>Output Signal Type</b>	Network stream, received by a paired AirMedia Series 3 receiver
<b>Input/Output Format</b>	2 channel LPCM

#### Connectors

<b>HDMI INPUT</b>	(1) HDMI Type A connector; HDMI digital video/audio input; Connect personal device for content sharing.
<b>USB2 TO HOST</b>	(1) USB-C connector, provides access to peripherals. Connect a USB-C to USB-A cable for use with devices without USB-C.

**USB2 / DP-S TO HOST** (1) USB-C connector, supports presentation using DisplayPort Alt-Mode and access to peripherals

**USB2 TO DEVICE** Reserved for future use

**MAIN PoE PD** (1) 8-pin RJ-45 connector; 100BASE-TX/1000BASE-T Ethernet port and PoE Class 0

**AUX PoE+ PSE** (1) 8-pin RJ-45 connector; 100BASE-TX/1000BASE-T Ethernet port and PoE+ Class 4;  
If enabled, connect a device such as a touch panel to provide passthrough network access. Provides PoE+ when the device is powered via DC power supply.

**24V 2.5A** (1) 2.1 x 5.5 mm DC power connector; 24VDC power input; [PW-2420RU](#) power pack sold separately

#### Controls and Indicators

**Power** (1) White LED, power supplied via the local power pack, PoE, or connected USB-C device

**MAIN LAN** (1) White LED, indicates a network connection on the Main network interface.

**AUX LAN** (1) White LED, indicates a network connection on the Auxillary network interface

**VIDEO IN** (1) White LED indicates the presence of a USB-C or HDMI video signal

**PERIPHERAL** (1) White LED indicates that conferencing peripherals are in use by the device

**SETUP** (1) White LED and (1) push button for pairing to an AirMedia Receiver

**RESET** (1) Recessed push button for restoring device to factory defaults

#### Power

**Power supply:** **USB:** Powered via USB-C connection to personal device, or  
**PoE:** IEEE 802.3af Class 0 Powered Device, or  
**Power Pack** (sold separately): Input 100-240VAC, 50/60 Hz; Output 2.5A @ 24VDC; Model: [PW-2420RU](#)

**Power Consumption (idle)** 4W

**Power Consumption (in use)** 12.5W

# AM-TX3-200

## AirMedia® Series 3 Connect Endpoint

**Power Consumption (in use and AUX PoE+ PSE passthrough)** 45W

### Environmental

**Temperature** 32° to 104°F (0° to 40°C)  
**Humidity** 10% to 90% RH (noncondensing)  
**Heat Dissipation** 47.5 BTU/hr

### Construction

**Chassis** Plastic, black finish, with (4) integrated mounting holes, vented sides  
**Mounting** Freestanding, surface mount  
**Mounting Bracket** Metal

### Dimensions (Device)

**Height** 1.18 in. (30 mm)  
**Width** 7.87 in. (200 mm)  
**Depth** 7.08 in. (180 mm)

### Dimensions (Device with Attached Mounting Bracket)

**Height** 1.26 in. (32 mm)  
**Width** 8.85 in. (225 mm)  
**Depth** 7.08 in. (180 mm)

### Weight

**Weight (device)** 21.06 oz (597 g)  
**Weight (mounting bracket)** 11.18 oz (317 g)

### Compliance

#### Regulatory Model: M202106002

Intertek® Listed for US & Canada, CE, IC, FCC Part 15 Class B digital device

#### AM-TX3-200

AirMedia® Series 3 Presentation Endpoint

### Available Accessories

For a list of available accessories, visit the [AM-TX3-200](#) product page.

#### Notes:

1. Wireless Conferencing functionality through the AirMedia Connect Endpoint requires a Wi-Fi network and Wireless Conferencing compatible AirMedia Series 3 Receiver.
2. The recommended compatible cables are [CBL-USB2-A-C-9](#), [CBL-USB2-A-C-12](#), [CBL-8K-HD-9](#), [CBL-8K-HD-12](#), and [CBL-USB3G1-C-C-9](#).
3. Crestron supports most mainstream devices and applications. For a list of supported conferencing peripherals, refer to [OLH Answer ID 1001764](#).

This product may be purchased from select authorized Crestron dealers and distributors. To find a dealer or distributor, please contact the Crestron sales representative for your area. A list of sales representatives is available online at [www.crestron.com/How-To-Buy/Find-a-Representative](#) or by calling 855-263-8754.

This product is covered under the Crestron standard limited warranty. Refer to [www.crestron.com/warranty](#) for full details.

The specific patents that cover Crestron products are listed online at [patents.crestron.com](#).

Certain Crestron products contain open source software. For specific information, please visit [www.crestron.com/opensource](#).

Crestron, the Crestron logo, AirMedia, Crestron Fusion, and XiO Cloud are either trademarks or registered trademarks of Crestron Electronics, Inc. in the United States and/or other countries. Apple and macOS are either trademarks or registered trademarks of Apple, Inc. in the United States and/or other countries. HDMI is either a trademark or registered trademark of HDMI Licensing LLC in the United States and/or other countries. Intertek is either a trademark or registered trademark of Intertek Group in the United States and/or other countries. Active Directory, Microsoft Teams, and Windows are either trademarks or registered trademarks of Microsoft Corporation in the United States and/or other countries. USB-C is either a trademark or registered trademark of USB Implementers Forum, Inc. in the United States and/or other countries. DisplayPort is either a trademark or registered trademark of Video Electronics Standards Association in the United States and/or other countries. Wi-Fi is either a trademark or registered trademark of Wi-Fi Alliance in the United States and/or other countries. Zoom Rooms is either a trademark or registered trademark of Zoom Video Communications, Inc. in the United States and/or other countries. Other trademarks, registered trademarks, and trade names may be used in this document to refer to either the entities claiming the marks and names or their products. Crestron disclaims any proprietary interest in the marks and names of others. Crestron is not responsible for errors in typography or photography.

Specifications are subject to change without notice.

©2025 Crestron Electronics, Inc.

Rev 04/25/25

# AM-TX3-200

AirMedia® Series 3 Connect Endpoint

# AM-TX3-200

AirMedia® Series 3 Connect Endpoint



# AM-TX3-200

## AirMedia® Series 3 Connect Endpoint

### Mounting Bracket

